

STANDALONE SMOKE DETECTOR**VS-S100 AC Powered Standalone Smoke Detector****KEY FEATURES**

- Battery Operated or AC Power
- Comply with standard of BS EN-54-5; UL539
- Photoelectric sensing technology
- Low battery run-out warning
- Alarm output with 85Db buzzer
- Built-in test button
- Interconnectability
- 57 (135°F) Fixed Rate

PARAMETERS

Operating voltage: 120VAC/230V/ 9V Battery
Interconnects: Up to 40PCS SMOKE ALARM
Alarm Horn output: 85dB at 10ft
Temperature Range: -10- +70
Humidity Range: 5%-95% relative humidity
Smoke Alarm Point: 2.06%/ft
Alarm temperature: 57° (135°F)
Dimension: 124 mm(Dia)*40mm(H)

**STANDALONE SMOKE DETECTOR****VS-S200 AC Powered Standalone Smoke Detector****KEY FEATURES**

- Hush function
- AC power supply, 9V battery backup
- Built-in hush button and test button
- Apply standard ENI4604
- Interconnects up to 40PCS SMOKE ALARM
- Battery run-out indicator
- Interconnectability
- Standard; ENI4604, UL217

PARAMETERS

Operating voltage: 220V AC/ 9V Battery
Temperature Range: 40°F to 100°F
Humidity Range: 5%-95% relative humidity (RH)
Alarm output: Sound and flash alarm
Sensitivity: 2.06%/ft
Sound level: 85dB/3 meters (10ft)
Interconnects: Up to 40pcs smoke alarm
Dimension: 128*38mm

